

# BP-150M

## Mobile Thermal Printer



### Applications



Shopping



Mart



Warehouse



Hospital



Logistics



Ticketing

[www.bopuson.com](http://www.bopuson.com)

## BP-150M Mobile Thermal Printer



| Specifications                         |                                |                                                                      |
|----------------------------------------|--------------------------------|----------------------------------------------------------------------|
| Printer Characteristics                | Printer Name                   | BP-150M                                                              |
|                                        | Printing Method                | Direct Thermal                                                       |
|                                        | Print Density                  | 384 dots/line                                                        |
|                                        | Printing Speed                 | 60-90mm/s                                                            |
|                                        | Maximum Printing Width         | 48mm                                                                 |
|                                        | Voice/Command Set              | ESC                                                                  |
| Memory                                 | RAM                            | 20K                                                                  |
|                                        | ROM                            | 2M                                                                   |
| Print Head                             | Print Head Life                | 50KM-100KM                                                           |
| Media Characteristics                  | Loading Method                 | Easy Paper Loading Structure                                         |
|                                        | Paper Type                     | Thermal Paper                                                        |
|                                        | Maximum Paper Width            | 58mm                                                                 |
|                                        | Media Thickness                | 0.05-0.15mm                                                          |
|                                        | Sensor Type                    | Photoelectric Sensor/Optocoupler Detection                           |
|                                        | Operating Temperature/Humidity | Temperature: 0°C-45°C<br>Humidity: 20%-90%                           |
| Operating Parameters                   | Storage Temperature/Humidity   | Temperature: -10°C-60°C<br>Humidity: 10%-90% (Excluding Paper Rolls) |
|                                        | Battery                        | 5V/1800mAh Rechargeable Polymer Lithium Battery                      |
| Electrical Specifications              | Charging Time                  | 3h                                                                   |
|                                        | Fully-Charged Working Time     | 100m                                                                 |
|                                        | Standby Time                   | 3days                                                                |
|                                        | Agency Certification Standards | CCC/CE/ROHS                                                          |
| Physical Parameters                    | Dimension(L*W*H)               | 112*81*156mm                                                         |
| Communication Interfaces and Functions | System Support Platform        | Android & iOS & Windows                                              |
|                                        | Standard Configuration         | USB(Type C)+Bluetooth                                                |
| Fonts/Graphics/Symbols                 | Character Size                 | 16*16, 24*24                                                         |
| Barcode Types                          | 1D                             | Code 39、Code 128                                                     |
|                                        | 2D                             | QRCODE                                                               |